

ACOUSTIC RATED DOORS AND FRAMES



ACOUSTIC



ACOUSTIC
GLAZING



SINGLE DOOR



PAIR DOOR



LISTED BY
INTERTEK



USA-MADE

CUSTOM OPTIONS:



FIRE RATED



POSITIVE
PRESSURE



TEMPERATURE
RISE



APPROVED
WITH SAFTI **FIRST**
GLAZING



SMOKE RATED

PRODUCT ADVANTAGES

- ▶ High Sound Transmission Class Rating (STC) up to 44 STC for use in recording studios, auditoriums, schools, offices, conference rooms, machinery enclosures, and other applications where noise abatement is required or desired.
- ▶ Standard door profiles include 6 in. door stile, 6 in. door top rail and 2 in. door frame. Narrow door profiles include 3-3/4 in. door stile, 3-3/4 in. door top rail and 1-1/8 in. door frame. Both the standard and narrow door profile options include a 10 in. ADA-compliant bottom rail, which can be modified with AHJ approval.
- ▶ Depending on glazing selection, door thickness ranges from 1-3/4 in. to 3 in.
- ▶ Available in single door or pairs.
- ▶ Available with fire ratings up to 90 minutes with positive pressure.
- ▶ USA-manufactured for fast lead times and competitive pricing.
- ▶ 5 year manufacturer's warranty.

DOOR CONSTRUCTION

Doors and door frames are made in 16-gauge A-60 steel. Door frames are shipped welded as standard and can be shipped knocked down upon request for ease of assembly in the field.

HARDWARE OPTIONS

Titan Metal Products offers standard hardware packages and can accommodate most specialty hardware options.



APPROVALS

ASTM E90, UL 10C, UL 10B, UL 1784, NFPA 80, NFPA 252, CAN/ULC-S104, CPSC 16 CFR 1201 Cat. I & II., ANSI Z97.1, HMMA 860, HMMA 861, HMMA 865

MEMBERSHIPS



© Titan Metal Products. February 2021



Titan Metal Products

USA

1-866-TITANMP (848-2667) | www.titanmetalproducts.com