

BUILDERS SERIES 3 HOUR TEMPERATURE RISE DOORS



FIRE RATED



POSITIVE PRESSURE



TEMPERATURE RISE



APPROVED WITH SAFTI **FIRST** GLAZING



SAFETY GLAZING



SMOKE RATED



SINGLE DOOR



PAIR DOOR



GREEN



LISTED BY INTERTEK



LISTED BY UL



USA-MADE

PRODUCT ADVANTAGES

- ▶ 3 hour temperature rise doors available in sizes up to 48 in. x 96 in. with vision lites up to 100 in.².
- ▶ Depending on glazing selection, door thickness ranges from 1-¾ in. to 3 in.
- ▶ For interior or exterior applications.
- ▶ Listed and labeled by UL and Intertek.
- ▶ USA-manufactured for fast lead times and competitive pricing.
- ▶ 5 year manufacturer's warranty.
- ▶ For specialty construction including dutch doors, please call **Titan Metal Products**.



SIZE CHART

Maximum Door Opening

Single Door	Pair Door
48 in. x 96 in. (1.21 m x 2.43 m)	96 in. x 96 in. (2.44 m x 2.44 m)

DOOR CONSTRUCTION

Doors and door frames are made in heavy duty steel and insulated to meet the 450° F temperature rise door requirements. Door frames are shipped welded as standard and can be shipped knocked down upon request for ease of assembly in the field.

HARDWARE OPTIONS

Titan Metal Products offers standard hardware packages and can accommodate most specialty hardware options.

APPROVALS

UL 10B, UL 10C, UL 1784, NFPA 80, NFPA 252, ASTM E152, ASTM E2074, CAN/ULC-S104, CPSC 16 CFR 1201 Cat. I. & II., ANSI Z97.1, HMMA 860, HMMA 861, HMMA 866

MEMBERSHIPS



© Titan Metal Products. February 2021



Titan Metal Products
USA

1-866-TITANMP (848-2667) | www.titanmetalproducts.com