# **BUILDERS SERIES 60-90 MINUTE TEMPERATURE RISE DOORS**











GLAZING





SINGLE DOOR











PRESSURE

TEMPERATURE RISE

WITH SAFTI FIRST GLAZING

SMOKE RATED

PAIR DOOR

LISTED BY UL

## **PRODUCT ADVANTAGES**

- ▶ 60-90 minute, full vision temperature rise doors tested and approved with clear SuperLite® II-XL fire resistive glazing by SAFTI FIRST®. For other available approved glazings, call **Titan Metal Products**.
- Easily integrates with GPX® Architectural Series wall system for a complete 1 to 2 hour fire resistive wall and door assembly.
- > Standard door profiles include 6 in. door stile, 6 in. door top rail and 2 in. door frame. Narrow door profiles include 3-3/4 in. door stile, 3-3/4 in. door top rail and 1-1/8 in. door frame. Both the standard and narrow door profile options include a 10 in. ADA-compliant bottom rail, which can be modified with AHJ approval.
- ▶ Depending on glazing selection, door thickness ranges from 1-¾ in. to 3 in.
- Doors up to 10 ft. tall for interior or exterior applications.
- Listed and labeled by UL and Intertek.
- USA-manufactured for fast lead times and competitive pricing.
- 5 year manufacturer's warranty.
- For specialty construction including dutch doors, please call Titan Metal Products.



## SIZE CHART

#### **Maximum Door Opening**

Single Door	Pair Door
54 in. x 120 in. (1.37 m x 3.05 m)*	96 in. x 120 in. (2.44 m x 3.05 m)*

<sup>\*</sup>For maximum door sizes, continuous hinges will be required.

# DOOR CONSTRUCTION

Doors and door frames are made in heavy duty steel and insulated to meet the 450° F temperature rise door requirements. Door frames are shipped welded as standard and can be shipped knocked down upon request for ease of assembly in the field.

#### HARDWARE OPTIONS


Titan Metal Products offers standard hardware packages and can accommodate most specialty hardware options.


# **APPROVALS**


UL 10B, UL 10C, UL 1784, NFPA 80, NFPA 252, ASTM E152, ASTM E2074, CAN/ULC-S104, CPSC 16 CFR 1201 Cat. I. & II., ANSI Z97.1, HMMA 860, HMMA 861, HMMA 866

# **BUILDERS SERIES 60-90 MINUTE TEMPERATURE RISE DOORS**

## **TYPICAL DETAILS**









DOOR TOP RAIL DETAIL

DOOR BOTTOM RAIL DETAIL

**DOOR MEETING STILES DETAIL** 



DOOR JAMB AT HINGE DETAIL



DOOR JAMB AT LOCK DETAIL

### **MEMBERSHIPS**





© Titan Metal Products. February 2021

