

HURRICANE RATED DOORS AND FRAMES



HURRICANE



SINGLE DOOR



PAIR DOOR



LISTED BY
INTERTEK



USA-MADE

CUSTOM OPTIONS:



FIRE RATED



POSITIVE
PRESSURE



TEMPERATURE
RISE



SMOKE RATED

PRODUCT ADVANTAGES

- ▶ Meets Structural Performance, Static Air Pressure, Cyclic Pressure and Missile Impact Protection for ASTM E330, ASTM 1886 and ASTM 1996.
- ▶ Available in single door or pairs.
- ▶ USA-manufactured for fast lead times and competitive pricing.
- ▶ 5 year manufacturer's warranty.

DOOR CONSTRUCTION

Doors

Flush 861 construction; Material thickness 16-gauge.

Frames

Welded 861 construction; Minimum 16-gauge thickness for single doors and minimum 14-gauge thickness for pair doors.



APPROVALS

ASTM E330, ASTM E1886, ASTM E1996, UL 1784

HARDWARE OPTIONS

Opening	Hurricane Approved Hardware
Single	Cylindrical lock
Single	Mortise lock
Single	Rim Exit
Opening	Hurricane Approved Hardware
Pair	Cylindrical lock/Manual Surface Bolts
Pair	Mortise lock/Manual Surface Bolts
Pair	Rim Exit Device x Rim Exit Device w/ Hardware Mullion
Pair	Concealed Vertical Rod x Surface Vertical Rod (to get CVR x CVR and SVR x SVR)

MEMBERSHIPS



© Titan Metal Products. February 2021



Titan Metal Products

USA

1-866-TITANMP (848-2667) | www.titanmetalproducts.com