

SMOKE RATED DOORS AND FRAMES



SMOKE RATED



SAFETY GLAZING



SINGLE DOOR



PAIR DOOR



GREEN



USA-MADE

PRODUCT ADVANTAGES

- ▶ S labeled doors meeting UL 1784, the Standard for Safety of Air Leakage Tests of Door Assemblies and other Opening Protectives.
- ▶ Complies with NFPA 105, Standard for Smoke Door Assemblies and other Opening Protectives.
- ▶ Standard door profiles include 6 in. door stile, 6 in. door top rail and 2 in. door frame. Narrow door profiles include 3-¾ in. door stile, 3-¾ in. door top rail and 1-⅞ in. door frame. Both the standard and narrow door profile options include a 10 in. ADA-compliant bottom rail, which can be modified with AHJ approval.
- ▶ Depending on glazing selection, door thickness ranges from 1-¾ in. to 3 in.
- ▶ Available in single door or pairs.
- ▶ USA-manufactured for fast lead times and competitive pricing.
- ▶ 5 year manufacturer's warranty.



DOOR CONSTRUCTION

Doors and door frames are made in 16-gauge A-60 steel. Door frames are shipped welded as standard and can be shipped knocked down upon request for ease of assembly in the field.

HARDWARE OPTIONS

Titan Metal Products offers standard hardware packages and can accommodate most specialty hardware options.

APPROVALS

UL 1784, NFPA 105, NFPA 80, HMMA 860, HMMA 861, HMMA 866, CPSC 16 CFR 1201 Cat. I & II., ANSI Z97.1

MEMBERSHIPS



© Titan Metal Products. February 2021



Titan Metal Products
USA

1-866-TITANMP (848-2667) | www.titanmetalproducts.com