

TITAN VISION KITS



FIRE RATED



POSITIVE PRESSURE



APPROVED WITH SAFTI **FIRST** GLAZING



SAFETY GLAZING



GREEN



LISTED BY UL



USA-MADE

PRODUCT ADVANTAGES

- ▶ Vision kits can be used in any 1- $\frac{3}{4}$ in. to 3 in. door thickness.
- ▶ Listed with fire ratings from 20-90 minutes (non-temperature rise or temperature rise) hollow metal, wood or composite doors.
- ▶ Clear view vision lite areas up to 3,288 in.².
- ▶ Can accommodate multiple glass thicknesses up to 3 in.
- ▶ Can be used with **SuperLite® I**, **SuperClear® 45-HS-LI (patent-pending)**, **SuperLite® X-45/60/90** and **SuperLite® II-XL** glazing by **SAFTI FIRST®**. For maximum sizes and other available approved glazings, call **Titan Metal Products**.
- ▶ Constructed in 20-gauge steel, corner keyed or welded. Comes with gasketing and countersunk mounting holes on the interior side.
- ▶ USA-manufactured for fast lead times and competitive pricing.
- ▶ 5 year manufacturer's warranty.



APPROVALS

NFPA 80, NFPA 252, UL 10C, CAN/ULC-S106, CPSC 16 CFR 1201, ANSI Z97.1

MEMBERSHIPS



© Titan Metal Products. February 2021



Titan Metal Products

USA

1-866-TITANMP (848-2667) | www.titanmetalproducts.com